

CIPEL Distribution S.A.

Route du Rhône 10 - CH-1963 Vétroz (Switzerland)
Phone : +41 27 565 7830 - Fax: +41 27 565 7840
e-mail : info@cipeldistribution.com - www.cipeldistribution.com

Multi Use releasable Press-pad

EPAPRESS-3L 600

The Product:

EPAPRESS-3L 600 is a "paper-clad" both sides releasable, white colour. The "paper-clad" is made of rein selected Cellulose mixed with some Cotton, laminated with two 25 μ release films. The main function is equalization of the applied pressure to get conformal homogeneous surface. It can control also the heat rise getting effective distribution on Z-axis. For each specific application the *Epapress-3L 600* might be reusable.

Applications:

Epapress-3L 600 is built up mainly for Lamination press-cycle control up to 195°C (380°F), in the production of Multilayer PCBs and Composites. It can be useful also in the rigid-flex ML press-cycles and cover layer for Flex-circuits. The results are in a controlled resin-flux, imbalance oversight across surfaces: uniformity.

Hydraulic-Press pressure range: 10 – 40 kg/cm²

Operating temperature: up to 195°C (380°F)

Material Properties

Available thickness:

0.6 , 0.9, 1,4 mm

Mass:

250 gr/m² (0.60mm thickness)

Colour:

white

